Epson EB-8H Series

# PRESENT SNARTLY

-

EPSON



### PERFECT PROJECTORS FOR PERFECT PRESENTATIONS

The Epson EB-8H Series has everything you need to give a successful presentation. Providing great images and innovative features, they are easy to use and highly energy efficient.

### Wide connectivity and new features

The Epson EB-8H Series provides many features to enhance the quality of your projection experience. These include microphone input and powerful integrated speaker for a large room; USB Direct connection, which allows you to plug in the new Epson Visualiser and project a source document or 3D objects directly, as well as normal projection from a PC onto a larger screen. And so that you can focus on your audience and your presentation, all of these features are accessible from the new remote control.

### Capitalise on your network

You can remotely configure and operate the projector over your network with ease, thanks to EasyMP Monitor. For example, you can set an email alert to monitor lamp status, and have advanced notice of any problems that could disrupt your presentation.

Thanks to its wide connectivity, mobility and easy, convenient features the Epson EB-8H Series is perfect for use in educational and corporate environments.

### Our contribution to the environment

The Epson EB-8H Series is designed and produced in compliance with our environmental policy. Energy efficiency is achieved with a long lamp-life. Add in easy maintenance and the result is a low total cost of ownership which makes these projectors particularly attractive.

### Environmentally friendly and cost-effective

- Minimises power consumption when not in use (timer functions, rapid power on/off)
- Reduces pollution: no paint used in production, 100% recyclable packaging
- Enjoys clear visibility in light rooms and save money thanks to the E-TORL lamp up to 6,000 hours lifetime in eco-mode

We are committed to providing the highest performance in our projectors by integrating innovative technologies.



Source Futuresource Consulting Ltd.



Without

With



3LCD technology provides superb image quality with smooth and natural colour reproduction.

### Colour Light Output, the new metric for projector brightness

Epson provides Colour Light Output specification data. Colour Light Output provides users with a simple, accurate and easy to understand way to evaluate projector colour performance.

## **COMPACT AND SMART**



 
 WXGA
 2500 lm
 10W
 2-in-1 S
 11
 11

### **PRODUCT SPECIFICATIONS**

SPECIFICATIONS	Epson EB-84L, Epson EB-84H -	Epson EB-825H	Epson EB-826WH			
	Epson EB-85H					
Projection system (3LCD)	0.63" (x3) Polysilicon	0.63'' (x3) Polysilicon	0.59" with MLA (x3) Polysilicon			
	TFT active matrix	TFT active matrix	TFT active matrix			
Native resolution	XGA (1024 x 768)	XGA (1024 x 768)	WXGA (1280 x 800)			
Native aspect ratio	4:3	4:3	16:10			
Resolution supported	VGA ~ UXGA	VGA ~ UXGA	VGA ~ UXGA			
White Light Output (brightness)**	EB-84L: 2,400 lm / 1,920 lm	3,000 lm / 2,400 lm	2,500 lm / 2,000 lm			
(Normal / eco)	EB-84H, EB-85H: 2,600 lm / 2,080 lm		2,000			
Colour Light Output (Normal /eco)	EB-84L: 2,400 lm / 1,920 lm	3,000 lm / 2,400 lm	2,500 lm / 2,000 lm			
	EB-84H, EB-85H: 2,600 lm / 2,080 lm					
PROJECTION LENS						
Throw ratio	1.38 - 2.24:1	1.38 - 2.24:1	1.38 - 2.24:1			
Focal length / F-number	18.2 mm - 29.2 mm / 1.49 - 1.94	18.2 mm - 29.2 mm / 1.49 - 1.94	18.2 mm - 29.2 mm / 1.49 - 1.94			
Focus / zoom type	Manual focus / 1.6 x Optical Zoom	Manual focus / 1.6 x Optical Zoom	Manual focus / 1.6 x Optical Zoom			
Offset	8.6:1	8.6:1	10:0			
LENS PROTECTION	A/V mute slide					
LAMP						
Туре	E-TORL 200W UHE					
Life (Eco / normal mode)	6,000 hours / 5,000 hours					
IMAGE						
Colour reproduction	Full-Colour (16.77 million colours)					
Fan noise (Eco / normal mode)	28 dB / 35 dB					
Contrast ratio**	2,000:1					
Screen size (Projection distance)	30" to 300" (0.84m - 13.9m) / EB-82	6WH : 29" to 280" (0.84m - 13.9m)				
Keystone correction	Vertical (automatic): ± 30 degrees	,				
INPUT						
Computer	2 x D-sub 15-pin (RGB), 1 x USB 2.0	) type B				
Video	2 x D-sub 15-pin (component), 1 x F					
Audio		ini-jack Microphone, 1 x Stereo RCA				
USB flash drive	1 x USB 2.0 type A *	initi-jack microphone, 1 x Stereo HOA				
Control	1 x RS232C (D-Sub 9pin)					
Network	LAN via RJ45					
OUTPUT	1 x D-sub 15-pin, 1 x Stereo mini-ja	ak out				
WIRELESS CONNECTION						
BUILT-IN SPEAKER	Optional wireless (802-11 a/b/g up to 54 mbps*) 10 W monaural					
DUILI-IN OF LARLIN						
DIDECT DOWED ON / OFF						
DIRECT POWER ON / OFF	Yes	ok bolo, password protoction, contro	I papal look			
DIRECT POWER ON / OFF SECURITY		ock hole, password protection, contro	l panel lock			
SECURITY	Improved security bar, kensington lo	• •	•			
	Improved security bar, kensington lo Auto source search, quick start, 8 co	ick hole, password protection, contro plour modes, microphone input, moni anced test patterns, user button on re	toring over network, SNMP,			
SECURITY	Improved security bar, kensington lo Auto source search, quick start, 8 co	blour modes, microphone input, moni anced test patterns, user button on re	toring over network, SNMP,			
SECURITY OTHER FUNCTIONS	Improved security bar, kensington lo Auto source search, quick start, 8 c user logo, freeze, e-zoom, help, adv resistant design, PC and Mac comp	olour modes, microphone input, moni anced test patterns, user button on re atible	toring over network, SNMP,			
SECURITY OTHER FUNCTIONS OPERATING TEMPERATURE /	Improved security bar, kensington lo Auto source search, quick start, 8 cr user logo, freeze, e-zoom, help, adv	olour modes, microphone input, moni anced test patterns, user button on re atible	toring over network, SNMP,			
SECURITY OTHER FUNCTIONS OPERATING TEMPERATURE / ALTITUDE	Improved security bar, kensington lo Auto source search, quick start, 8 c user logo, freeze, e-zoom, help, adv resistant design, PC and Mac comp	olour modes, microphone input, moni anced test patterns, user button on re atible	toring over network, SNMP,			
SECURITY OTHER FUNCTIONS OPERATING TEMPERATURE / ALTITUDE POWER REQUIREMENTS	Improved security bar, kensington Ic Auto source search, quick start, 8 cr user logo, freeze, e-zoom, help, adv resistant design, PC and Mac comp 5°C to 35°C / 0 to 2,286 m (High alti	olour modes, microphone input, moni anced test patterns, user button on re atible	toring over network, SNMP,			
SECURITY OTHER FUNCTIONS OPERATING TEMPERATURE / ALTITUDE POWER REQUIREMENTS Power supply wattage	Improved security bar, kensington Ic Auto source search, quick start, 8 cr user logo, freeze, e-zoom, help, adv resistant design, PC and Mac comp 5°C to 35°C / 0 to 2,286 m (High alti 100 - 240 V AC ±10%, 50/60 Hz	olour modes, microphone input, moni anced test patterns, user button on re atible	toring over network, SNMP,			
SECURITY OTHER FUNCTIONS OPERATING TEMPERATURE / ALITUDE POWER REQUIREMENTS Power supply wattage Power consumption lamp on	Improved security bar, kensington Ic Auto source search, quick start, 8 cc user logo, freeze, e-zoom, help, adv resistant design, PC and Mac comp 5°C to 35°C / 0 to 2,286 m (High alti 100 - 240 V AC ±10%, 50/60 Hz 228W (eco)	olour modes, microphone input, moni anced test patterns, user button on re atible	toring over network, SNMP,			
SECURITY OTHER FUNCTIONS OPERATING TEMPERATURE / ALTITUDE POWER REQUIREMENTS Power supply wattage Power consumption lamp on Power consumption stand-by	Improved security bar, kensington Ic Auto source search, quick start, 8 cr user logo, freeze, e-zoom, help, adv resistant design, PC and Mac comp 5°C to 35°C / 0 to 2,286 m (High alti 100 - 240 V AC ±10%, 50/60 Hz	olour modes, microphone input, moni anced test patterns, user button on re atible	toring over network, SNMP,			
SECURITY OTHER FUNCTIONS OPERATING TEMPERATURE / ALTITUDE POWER REQUIREMENTS Power supply wattage Power consumption lamp on Power consumption stand-by WEIGHT AND DIMENSION	Improved security bar, kensington Ic Auto source search, quick start, 8 c user logo, freeze, e-zoom, help, adv resistant design, PC and Mac comp 5°C to 35°C / 0 to 2,286 m (High alti 100 - 240 V AC ±10%, 50/60 Hz 228W (eco) 0.7W (eco)	olour modes, microphone input, moni anced test patterns, user button on re atible	toring over network, SNMP,			
SECURITY OTHER FUNCTIONS OPERATING TEMPERATURE / ALTITUDE POWER REQUIREMENTS Power supply wattage Power consumption lamp on Power consumption stand-by WEIGHT AND DIMENSION Weight	Improved security bar, kensington Ic Auto source search, quick start, 8 cr user logo, freeze, e-zoom, help, adv resistant design, PC and Mac comp 5°C to 35°C / 0 to 2,286 m (High alti 100 - 240 V AC ±10%, 50/60 Hz 228W (eco) 0.7W (eco) 3.1 kg	olour modes, microphone input, moni anced test patterns, user button on re atible	toring over network, SNMP,			
SECURITY OTHER FUNCTIONS OPERATING TEMPERATURE / ALITIUDE POWER REQUIREMENTS Power supply wattage Power consumption lamp on Power consumption stand-by WEIGHT AND DIMENSION Weight Dimension (D x W x H)	Improved security bar, kensington Ic Auto source search, quick start, 8 cd user logo, freeze, e-zoom, help, adv resistant design, PC and Mac comp 5°C to 35°C / 0 to 2,286 m (High alti 100 - 240 V AC ±10%, 50/60 Hz 228W (eco) 0.7W (eco) 3.1 kg 250 x 327 x 95 mm (excluding feet)	olour modes, microphone input, moni anced test patterns, user button on re atible tude mode over 1,500 m)	toring over network, SNMP, emote control, improved dust			
SECURITY OTHER FUNCTIONS OPERATING TEMPERATURE / ALTITUDE POWER REQUIREMENTS Power supply wattage Power consumption lamp on Power consumption stand-by WEIGHT AND DIMENSION Weight	Improved security bar, kensington Ic Auto source search, quick start, 8 c user logo, freeze, e-zoom, help, adv resistant design, PC and Mac comp 5°C to 35°C / 0 to 2,286 m (High alti 100 - 240 V AC ±10%, 50/60 Hz 228W (eco) 0.7W (eco) 3.1 kg 250 x 327 x 95 mm (excluding feet) 34 languages: English / French / Ge	olour modes, microphone input, moni anced test patterns, user button on re atible tude mode over 1,500 m) rman / Italian / Spanish / Catalan / Po	toring over network, SNMP, emote control, improved dust			
SECURITY OTHER FUNCTIONS OPERATING TEMPERATURE / ALITIUDE POWER REQUIREMENTS Power supply wattage Power consumption lamp on Power consumption stand-by WEIGHT AND DIMENSION Weight Dimension (D x W x H)	Improved security bar, kensington Ic Auto source search, quick start, 8 cr user logo, freeze, e-zoom, help, adv resistant design, PC and Mac comp 5°C to 35°C / 0 to 2,286 m (High alti 100 - 240 V AC ±10%, 50/60 Hz 228W (eco) 0.7W (eco) 3.1 kg 250 x 327 x 95 mm (excluding feet) 34 languages: English / French / Ge Hungarian / Czech / Romanian / Slc	olour modes, microphone input, moni anced test patterns, user button on re atible tude mode over 1,500 m) man / Italian / Spanish / Catalan / Po venian / Norwegian / Swedish / Finni	toring over network, SNMP, emote control, improved dust rtuguese / Dutch / Danish / Polish / sh / Russian / Ukrainian / Greek /			
SECURITY OTHER FUNCTIONS OPERATING TEMPERATURE / ALITIUDE POWER REQUIREMENTS Power supply wattage Power consumption lamp on Power consumption stand-by WEIGHT AND DIMENSION Weight Dimension (D x W x H)	Improved security bar, kensington Ic Auto source search, quick start, 8 cr user logo, freeze, e-zoom, help, adv resistant design, PC and Mac comp 5°C to 35°C / 0 to 2,286 m (High alti 100 - 240 V AC ±10%, 50/60 Hz 228W (eco) 0.7W (eco) 3.1 kg 250 x 327 x 95 mm (excluding feet) 34 languages: English / French / Ge Hungarian / Czech / Romanian / Slc	olour modes, microphone input, moni anced test patterns, user button on re atible tude mode over 1,500 m) man / Italian / Spanish / Catalan / Po venian / Norvegian / Swedish / Finni Bulgarian / Malay / Wetnamese / Het	toring over network, SNMP, emote control, improved dust rtuguese / Dutch / Danish / Polish / sh / Russian / Ukrainian / Greek /			
SECURITY OTHER FUNCTIONS OPERATING TEMPERATURE / ALITIUDE POWER REQUIREMENTS Power supply wattage Power consumption lamp on Power consumption stand-by WEIGHT AND DIMENSION Weight Dimension (D x W x H)	Improved security bar, kensington Ic Auto source search, quick start, 8 cd user logo, freeze, e-zoom, help, adv resistant design, PC and Mac comp 5°C to 35°C / 0 to 2,286 m (High alti 100 - 240 V AC ±10%, 50/60 Hz 228W (eco) 0.7W (eco) 3.1 kg 250 x 327 x 95 mm (excluding feet) 34 languages: English / French / Ge Hungarian / Czech / Romanian / Slovak / Turkish / Arabic / Croatian / Slovak /	olour modes, microphone input, moni anced test patterns, user button on re atible tude mode over 1,500 m) man / Italian / Spanish / Catalan / Po venian / Norvegian / Swedish / Finni Bulgarian / Malay / Wetnamese / Het	toring over network, SNMP, emote control, improved dust rtuguese / Dutch / Danish / Polish / sh / Russian / Ukrainian / Greek /			
SECURITY OTHER FUNCTIONS OPERATING TEMPERATURE / ALTITUDE POWER REQUIREMENTS Power supply wattage Power consumption lamp on Power consumption stand-by WEIGHT AND DIMENSION Weight Dimension (D x W x H) ON-SCREEN MENU	Improved security bar, kensington Ic Auto source search, quick start, 8 cd user logo, freeze, e-zoom, help, adv resistant design, PC and Mac comp 5°C to 35°C / 0 to 2,286 m (High alti 100 - 240 V AC ±10%, 50/60 Hz 228W (eco) 0.7W (eco) 3.1 kg 250 x 327 x 95 mm (excluding feet) 34 languages: English / French / Ge Hungarian / Czech / Romanian / Slovak / Turkish / Arabic / Croatian / Slovak /	olour modes, microphone input, moni anced test patterns, user button on re atible tude mode over 1,500 m) man / Italian / Spanish / Catalan / Po venian / Norvegian / Swedish / Finni Bulgarian / Malay / Wetnamese / Het	toring over network, SNMP, emote control, improved dust rtuguese / Dutch / Danish / Polish / sh / Russian / Ukrainian / Greek /			
SECURITY OTHER FUNCTIONS OPERATING TEMPERATURE / ALITIUDE POWER REQUIREMENTS Power supply wattage Power consumption lamp on Power consumption stand-by WEIGHT AND DIMENSION Weight Dimension (D x W x H)	Improved security bar, kensington Ic Auto source search, quick start, 8 cd user logo, freeze, e-zoom, help, adv resistant design, PC and Mac comp 5°C to 35°C / 0 to 2,286 m (High alti 100 - 240 V AC ±10%, 50/60 Hz 228W (eco) 0.7W (eco) 3.1 kg 250 x 327 x 95 mm (excluding feet) 34 languages: English / French / Ge Hungarian / Czech / Romanian / Slovak / Turkish / Arabic / Croatian / Slovak /	olour modes, microphone input, moni anced test patterns, user button on re atible tude mode over 1,500 m) man / Italian / Spanish / Catalan / Po venian / Norvegian / Swedish / Finni Bulgarian / Malay / Wetnamese / Het	toring over network, SNMP, emote control, improved dust rtuguese / Dutch / Danish / Polish / sh / Russian / Ukrainian / Greek /			
SECURITY OTHER FUNCTIONS OPERATING TEMPERATURE / ALITUDE POWER REQUIREMENTS Power supply wattage Power consumption lamp on Power consumption stand-by WEIGHT AND DIMENSION Weight Dimension (D x W x H) ON-SCREEN MENU SUPPLIED ACCESSORIES Power cable	Improved security bar, kensington Ic Auto source search, quick start, 8 c user logo, freeze, e-zoom, help, adv resistant design, PC and Mac comp 5°C to 35°C / 0 to 2,286 m (High alti 100 - 240 V AC ±10%, 50/60 Hz 228W (eco) 0.7W (eco) 3.1 kg 250 x 327 x 95 mm (excluding feet) 34 languages: English / French / Ge Hungarian / Czech / Romanian / Slo Turkish / Arabic / Croatian / Slovak / Chinese / traditional Chinese / Korea	olour modes, microphone input, moni anced test patterns, user button on re atible tude mode over 1,500 m) man / Italian / Spanish / Catalan / Po venian / Norvegian / Swedish / Finni Bulgarian / Malay / Wetnamese / Het	toring over network, SNMP, emote control, improved dust rtuguese / Dutch / Danish / Polish / sh / Russian / Ukrainian / Greek /			
SECURITY OTHER FUNCTIONS OPERATING TEMPERATURE / ALITTUDE POWER REQUIREMENTS Power supply wattage Power consumption lamp on Power consumption stand-by WEIGHT AND DIMENSION Weight Dimension (D x W x H) ON-SCREEN MENU SUPPLIED ACCESSORIES	Improved security bar, kensington Ic Auto source search, quick start, 8 cd user logo, freeze, e-zoom, help, adv resistant design, PC and Mac comp 5°C to 35°C / 0 to 2,286 m (High alti 100 - 240 V AC ±10%, 50/60 Hz 228W (eco) 0.7W (eco) 3.1 kg 250 x 327 x 95 mm (excluding feet) 34 languages: English / French / Ge Hungarian / Czech / Romanian / Slovak / Chinese / traditional Chinese / Korea 3 m	olour modes, microphone input, moni anced test patterns, user button on re atible tude mode over 1,500 m) man / Italian / Spanish / Catalan / Po venian / Norvegian / Swedish / Finni Bulgarian / Malay / Wetnamese / Het	toring over network, SNMP, emote control, improved dust rtuguese / Dutch / Danish / Polish / sh / Russian / Ukrainian / Greek /			
SECURITY OTHER FUNCTIONS OPERATING TEMPERATURE / ALTITUDE POWER REQUIREMENTS Power supply wattage Power consumption lamp on Power consumption stand-by WEIGHT AND DIMENSION Weight Dimension (D x W x H) ON-SCREEN MENU SUPPLIED ACCESSORIES Power cable Computer cable USB cable	Improved security bar, kensington Ic Auto source search, quick start, 8 cr user logo, freeze, e-zoom, help, adv resistant design, PC and Mac comp 5°C to 35°C / 0 to 2,286 m (High alti 100 - 240 V AC ±10%, 50/60 Hz 228W (eco) 0.7W (eco) 3.1 kg 250 x 327 x 95 mm (excluding feet) 34 languages: English / French / Ge Hungarian / Czech / Romanian / Slo Turkish / Arabic / Croatian / Slovak / Chinese / traditional Chinese / Kores 3 m 1.8 m D-sub 15pin (Male / Male) 1.8 m USB-A to USB-B	olour modes, microphone input, moni anced test patterns, user button on re atible tude mode over 1,500 m) man / Italian / Spanish / Catalan / Po venian / Norvegian / Swedish / Finni Bulgarian / Malay / Wetnamese / Het	toring over network, SNMP, emote control, improved dust rtuguese / Dutch / Danish / Polish / sh / Russian / Ukrainian / Greek /			
SECURITY OTHER FUNCTIONS OPERATING TEMPERATURE / ALITTUDE POWER REQUIREMENTS Power supply wattage Power consumption lamp on Power consumption stand-by WEIGHT AND DIMENSION Weight Dimension (D x W x H) ON-SCREEN MENU SUPPLIED ACCESSORIES Power cable Computer cable USB cable Soft carry case	Improved security bar, kensington Ic Auto source search, quick start, 8 c user logo, freeze, e-zoom, help, adv resistant design, PC and Mac comp 5°C to 35°C / 0 to 2,286 m (High alti 100 - 240 V AC ±10%, 50/60 Hz 228W (eco) 0.7W (eco) 3.1 kg 250 x 327 x 95 mm (excluding feet) 34 languages: English / French / Ge Hungarian / Czech / Romanian / Slo Turkish / Arabic / Croatian / Slovak / Chinese / traditional Chinese / Korea 3 m 1.8 m D-sub 15pin (Male / Male) 1.8 m USB-A to USB-B included	olour modes, microphone input, moni anced test patterns, user button on re atible tude mode over 1,500 m) man / Italian / Spanish / Catalan / Po venian / Norvegian / Swedish / Finni Bulgarian / Malay / Wetnamese / Het	toring over network, SNMP, emote control, improved dust rtuguese / Dutch / Danish / Polish / sh / Russian / Ukrainian / Greek /			
SECURITY OTHER FUNCTIONS OPERATING TEMPERATURE / ALITIUDE POWER REQUIREMENTS Power supply wattage Power consumption lamp on Power consumption stand-by WEIGHT AND DIMENSION Weight Dimension (D x W x H) ON-SCREEN MENU SUPPLIED ACCESSORIES Power cable Computer cable USB cable Soft carry case Remote control	Improved security bar, kensington Ic Auto source search, quick start, 8 cd user logo, freeze, e-zoom, help, adv resistant design, PC and Mac comp 5°C to 35°C / 0 to 2,286 m (High alti 100 - 240 V AC ±10%, 50/60 Hz 228W (eco) 0.7W (eco) 3.1 kg 250 x 327 x 95 mm (excluding feet) 34 languages: English / French / Ge Hungarian / Czech / Romanian / Slovak / Chinese / traditional Chinese / Korea 3 m 1.8 m D-sub 15pin (Male / Male) 1.8 m USB-A to USB-B included included with 2 x AA type batteries	olour modes, microphone input, moni anced test patterns, user button on re atible tude mode over 1,500 m) man / Italian / Spanish / Catalan / Po venian / Norvegian / Swedish / Finni Bulgarian / Malay / Wetnamese / Het	toring over network, SNMP, emote control, improved dust rtuguese / Dutch / Danish / Polish / sh / Russian / Ukrainian / Greek /			
SECURITY OTHER FUNCTIONS OPERATING TEMPERATURE / ALITIUDE POWER REQUIREMENTS Power consumption lamp on Power consumption stand-by WEIGHT AND DIMENSION Weight Dimension (D x W x H) ON-SCREEN MENU SUPPLIED ACCESSORIES Power cable Computer cable USB cable Soft carry case Remote control Epson projector software (cD-ROM)	Improved security bar, kensington Ic Auto source search, quick start, 8 c user logo, freeze, e-zoom, help, adv resistant design, PC and Mac comp 5°C to 35°C / 0 to 2,286 m (High alti 100 - 240 V AC ±10%, 50/60 Hz 228W (eco) 0.7W (eco) 3.1 kg 250 x 327 x 95 mm (excluding feet) 34 languages: English / French / Ge Hungarian / Czech / Romanian / Slo Turkish / Arabic / Croatian / Slovak / Chinese / traditional Chinese / Korea 3 m 1.8 m D-sub 15pin (Male / Male) 1.8 m USB-A to USB-B included included with 2 x AA type batteries included	olour modes, microphone input, moni anced test patterns, user button on re atible tude mode over 1,500 m) man / Italian / Spanish / Catalan / Po venian / Norvegian / Swedish / Finni Bulgarian / Malay / Wetnamese / Het	toring over network, SNMP, emote control, improved dust rtuguese / Dutch / Danish / Polish / sh / Russian / Ukrainian / Greek /			
SECURITY OTHER FUNCTIONS OPERATING TEMPERATURE / ALITIUDE POWER REQUIREMENTS Power supply wattage Power consumption lamp on Power consumption stand-by WEIGHT AND DIMENSION Weight Dimension (D x W x H) ON-SCREEN MENU SUPPLIED ACCESSORIES Power cable Computer cable USB cable Soft carry case Remote control	Improved security bar, kensington Ic Auto source search, quick start, 8 cd user logo, freeze, e-zoom, help, adv resistant design, PC and Mac comp 5°C to 35°C / 0 to 2,286 m (High alti 100 - 240 V AC ±10%, 50/60 Hz 228W (eco) 0.7W (eco) 3.1 kg 250 x 327 x 95 mm (excluding feet) 34 languages: English / French / Ge Hungarian / Czech / Romanian / Slovak / Chinese / traditional Chinese / Korea 3 m 1.8 m D-sub 15pin (Male / Male) 1.8 m USB-A to USB-B included included with 2 x AA type batteries	olour modes, microphone input, moni anced test patterns, user button on re atible tude mode over 1,500 m) man / Italian / Spanish / Catalan / Po venian / Norvegian / Swedish / Finni Bulgarian / Malay / Wetnamese / Het	toring over network, SNMP, emote control, improved dust rtuguese / Dutch / Danish / Polish / sh / Russian / Ukrainian / Greek /			
SECURITY OTHER FUNCTIONS OPERATING TEMPERATURE / ALITTUDE POWER REQUIREMENTS Power supply wattage Power consumption lamp on Power consumption stand-by WEIGHT AND DIMENSION Weight Dimension (D x W x H) ON-SCREEN MENU SUPPLIED ACCESSORIES Power cable Computer cable USB cable Soft carry case Remote control Epson projector software (cD-ROM) Password protect sticker	Improved security bar, kensington Ic Auto source search, quick start, 8 cr user logo, freeze, e-zoom, help, adv resistant design, PC and Mac comp 5°C to 35°C / 0 to 2,286 m (High alti 100 - 240 V AC ±10%, 50/60 Hz 228W (eco) 0.7W (eco) 3.1 kg 250 x 327 x 95 mm (excluding feet), 34 languages: English / French / Ge Hungarian / Czech / Romanian / Slc Turkish / Arabic / Croatian / Slovak / Chinese / traditional Chinese / Korea 3 m 1.8 m D-sub 15pin (Male / Male) 1.8 m USB-A to USB-B included included with 2 x AA type batteries included	olour modes, microphone input, moni anced test patterns, user button on re atible tude mode over 1,500 m) man / Italian / Spanish / Catalan / Po venian / Norvegian / Swedish / Finni Bulgarian / Malay / Wetnamese / Het	toring over network, SNMP, emote control, improved dust rtuguese / Dutch / Danish / Polish / sh / Russian / Ukrainian / Greek /			
SECURITY OTHER FUNCTIONS OPERATING TEMPERATURE / ALITTUDE POWER REQUIREMENTS Power supply wattage Power consumption lamp on Power consumption stand-by WEIGHT AND DIMENSION Weight Dimension (D x W x H) ON-SCREEN MENU SUPPLIED ACCESSORIES Power cable Computer cable USB cable Soft carry case Remote control Epson projector software (cD-ROM) Password protect sticker USer manual OPTIONAL ACCESSORIES	Improved security bar, kensington Ic Auto source search, quick start, 8 cd user logo, freeze, e-zoom, help, adv resistant design, PC and Mac comp 5°C to 35°C / 0 to 2,286 m (High alti 100 - 240 V AC ±10%, 50/60 Hz 228W (eco) 0.7W (eco) 3.1 kg 250 x 327 x 95 mm (excluding feet) 34 languages: English / French / Ge Hungarian / Czech / Romaina / Slovak / Chinese / traditional Chinese / Korea 3 m 1.8 m D-sub 15pin (Male / Male) 1.8 m USB-A to USB-B included included with 2 x AA type batteries included included	olour modes, microphone input, moni anced test patterns, user button on re atible tude mode over 1,500 m) man / Italian / Spanish / Catalan / Po venian / Norvegian / Swedish / Finni Bulgarian / Malay / Wetnamese / Het	toring over network, SNMP, emote control, improved dust rtuguese / Dutch / Danish / Polish / sh / Russian / Ukrainian / Greek /			
SECURITY OTHER FUNCTIONS OPERATING TEMPERATURE / ALTITUDE POWER REQUIREMENTS Power consumption lamp on Power consumption stand-by WEIGHT AND DIMENSION Weight Dimension (D x W x H) ON-SCREEN MENU SUPPLIED ACCESSORIES Power cable Computer cable USB cable Soft carry case Remote control Epson projector software (cD-ROM) Password protect sticker User manual OPTIONAL ACCESSORIES Wireless LAN unit (a/b/g)	Improved security bar, kensington Ic Auto source search, quick start, 8 c user logo, freeze, e-zoom, help, adv resistant design, PC and Mac comp 5°C to 35°C / 0 to 2,286 m (High alti 100 - 240 V AC ±10%, 50/60 Hz 228W (eco) 0.7W (eco) 3.1 kg 250 x 327 x 95 mm (excluding feet) 34 languages: English / French / Ge Hungarian / Czech / Romanian / Slovak / Chinese / traditional Chinese / Korea 3 m 1.8 m D-sub 15pin (Male / Male) 1.8 m USB-A to USB-B included included included included included ELPAP03 *	olour modes, microphone input, moni anced test patterns, user button on re atible tude mode over 1,500 m) man / Italian / Spanish / Catalan / Po venian / Norvegian / Swedish / Finni Bulgarian / Malay / Wetnamese / Het	toring over network, SNMP, emote control, improved dust rtuguese / Dutch / Danish / Polish / sh / Russian / Ukrainian / Greek /			
SECURITY OTHER FUNCTIONS OPERATING TEMPERATURE / ALITTUDE POWER REQUIREMENTS Power supply wattage Power consumption lamp on Power consumption lamp on Power consumption stand-by WEIGHT AND DIMENSION Weight Dimension (D x W x H) ON-SCREEN MENU SUPPLIED ACCESSORIES Power cable Computer cable USB cable Soft carry case Remote control Epson projector software (cD-ROM) Password protect sticker User manual OPTIONAL ACCESSORIES Wireless LAN unit (a/b/g) Quick Wi-Fi connection USB key	Improved security bar, kensington Ic Auto source search, quick start, 8 c user logo, freeze, e-zoom, help, adv resistant design, PC and Mac comp 5°C to 35°C / 0 to 2,286 m (High alti 100 - 240 V AC ±10%, 50/60 Hz 228W (eco) 0.7W (eco) 3.1 kg 250 x 327 x 95 mm (excluding feet) 34 languages: English / French / Ge Hungarian / Czech / Romanian / Slc Turkish / Arabic / Croatian / Slovak / Chinese / traditional Chinese / Korea 3 m 1.8 m D-sub 15pin (Male / Male) 1.8 m USB-A to USB-B included included included included ELPAP03 * ELPAP03 *	olour modes, microphone input, moni anced test patterns, user button on re atible tude mode over 1,500 m) man / Italian / Spanish / Catalan / Po venian / Norvegian / Swedish / Finni Bulgarian / Malay / Wetnamese / Het	toring over network, SNMP, emote control, improved dust rtuguese / Dutch / Danish / Polish / sh / Russian / Ukrainian / Greek /			
SECURITY OTHER FUNCTIONS OPERATING TEMPERATURE / ALTITUDE POWER REQUIREMENTS Power consumption lamp on Power consumption stand-by WEIGHT AND DIMENSION Weight Dimension (D x W x H) ON-SCREEN MENU SUPPLIED ACCESSORIES Power cable Computer cable USB cable Soft carry case Remote control Epson projector software (cD-ROM) Password protect sticker User manual OPTIONAL ACCESSORIES Wireless LAN unit (a/b/g)	Improved security bar, kensington Ic Auto source search, quick start, 8 c user logo, freeze, e-zoom, help, adv resistant design, PC and Mac comp 5°C to 35°C / 0 to 2,286 m (High alti 100 - 240 V AC ±10%, 50/60 Hz 228W (eco) 0.7W (eco) 3.1 kg 250 x 327 x 95 mm (excluding feet) 34 languages: English / French / Ge Hungarian / Czech / Romanian / Slo Turkish / Arabic / Croatian / Slovak / Chinese / traditional Chinese / Korea 3 m 1.8 m D-sub 15pin (Male / Male) 1.8 m USB-A to USB-B included included included included included ELPAP03 * ELPAP05 * ELPAP05 *	olour modes, microphone input, moni anced test patterns, user button on re atible tude mode over 1,500 m) man / Italian / Spanish / Catalan / Po venian / Norvegian / Swedish / Finni Bulgarian / Malay / Wetnamese / Het	toring over network, SNMP, emote control, improved dust rtuguese / Dutch / Danish / Polish / sh / Russian / Ukrainian / Greek /			
SECURITY OTHER FUNCTIONS OPERATING TEMPERATURE / ALITTUDE POWER REQUIREMENTS Power supply wattage Power consumption lamp on Power consumption stand-by WEIGHT AND DIMENSION Weight Dimension (D x W x H) ON-SCREEN MENU SUPPLIED ACCESSORIES Power cable Computer cable USB cable Soft carry case Remote control Epson projector software (cD-ROM) Password protect sticker User manual OPTIONAL ACCESSORIES Wireless LAN unit (a/b/g) Quick Wi-Fi connection USB key Visualiser Lamp	Improved security bar, kensington Ic Auto source search, quick start, 8 c user logo, freeze, e-zoom, help, adv resistant design, PC and Mac comp 5°C to 35°C / 0 to 2,286 m (High alti 100 - 240 V AC ±10%, 50/60 Hz 228W (eco) 0.7W (eco) 3.1 kg 250 x 327 x 95 mm (excluding feet) 34 languages: English / French / Ge Hungarian / Czech / Romaina / Slovak / Chinese / traditional Chinese / Korea 3 m 1.8 m D-sub 15pin (Male / Male) 1.8 m USB-A to USB-B included included with 2 x AA type batteries included included included ELPAP03 * ELPAP03 * ELPAP05 *	olour modes, microphone input, moni anced test patterns, user button on re atible tude mode over 1,500 m) man / Italian / Spanish / Catalan / Po venian / Norvegian / Swedish / Finni Bulgarian / Malay / Wetnamese / Het	toring over network, SNMP, emote control, improved dust rtuguese / Dutch / Danish / Polish / sh / Russian / Ukrainian / Greek /			
SECURITY OTHER FUNCTIONS OPERATING TEMPERATURE / ALITUDE POWER REQUIREMENTS Power supply wattage Power consumption lamp on Power consumption stand-by WEIGHT AND DIMENSION Weight Dimension (D x W x H) ON-SCREEN MENU SUPPLIED ACCESSORIES Power cable Computer cable USB cable Soft carry case Remote control Epson projector software (cD-ROM) Password protect sticker User manual OPTIONAL ACCESSORIES Wireless LAN unit (a/b/g) Quick Wi-Fi connection USB key Visualiser Lamp Filter	Improved security bar, kensington Ic Auto source search, quick start, 8 c user logo, freeze, e-zoom, help, adv resistant design, PC and Mac comp 5°C to 35°C / 0 to 2,286 m (High alti 100 - 240 V AC ±10%, 50/60 Hz 228W (eco) 0.7W (eco) 3.1 kg 250 x 327 x 95 mm (excluding feet) 34 languages: English / French / Ge Hungarian / Czech / Romanian / Slovak / Chinese / traditional Chinese / Korea 3 m 1.8 m D-sub 15pin (Male / Male) 1.8 m USB-A to USB-B included included included included included included included ELPAP03 * ELPAP05 * ELPAP50 ELPAF22	olour modes, microphone input, moni anced test patterns, user button on re atible tude mode over 1,500 m) man / Italian / Spanish / Catalan / Po venian / Norvegian / Swedish / Finni Bulgarian / Malay / Wetnamese / Het	toring over network, SNMP, emote control, improved dust rtuguese / Dutch / Danish / Polish / sh / Russian / Ukrainian / Greek /			
SECURITY OTHER FUNCTIONS OPERATING TEMPERATURE / ALITTUDE POWER REQUIREMENTS Power supply wattage Power consumption lamp on Power consumption stand-by WEIGHT AND DIMENSION Weight Dimension (D x W x H) ON-SCREEN MENU SUPPLIED ACCESSORIES Power cable Computer cable USB cable Soft carry case Remote control Epson projector software (cD-ROM) Password protect sticker User manual OPTIONAL ACCESSORIES Wireless LAN unit (a/b/g) Quick Wi-Fi connection USB key Visualiser Lamp	Improved security bar, kensington Ic Auto source search, quick start, 8 c user logo, freeze, e-zoom, help, adv resistant design, PC and Mac comp 5°C to 35°C / 0 to 2,286 m (High alti 100 - 240 V AC ±10%, 50/60 Hz 228W (eco) 0.7W (eco) 3.1 kg 250 x 327 x 95 mm (excluding feet) 34 languages: English / French / Ge Hungarian / Czech / Romanian / Slc Turkish / Arabic / Croatian / Slovak / Chinese / traditional Chinese / Korea 3 m 1.8 m D-sub 15pin (Male / Male) 1.8 m USB-A to USB-B included included included included included ELPAP03 * ELPAP05 * ELPDC06 * ELPLP50 ELPAF22 ELPMB23	olour modes, microphone input, moni anced test patterns, user button on re atible tude mode over 1,500 m) man / Italian / Spanish / Catalan / Po venian / Norvegian / Swedish / Finni Bulgarian / Malay / Wetnamese / Het	toring over network, SNMP, emote control, improved dust rtuguese / Dutch / Danish / Polish / sh / Russian / Ukrainian / Greek /			
SECURITY OTHER FUNCTIONS OPERATING TEMPERATURE / ALITTUDE POWER REQUIREMENTS Power supply wattage Power consumption lamp on Power consumption stand-by WEIGHT AND DIMENSION Weight Dimension (D x W x H) ON-SCREEN MENU SUPPLIED ACCESSORIES Power cable Computer cable USB cable Soft carry case Remote control Epson projector software (cD-ROM) Password protect sticker User manual OPTIONAL ACCESSORIES Wireless LAN unit (a/b/g) Quick Wi-Fi connection USB key Visualiser Lamp Filter Ceiling mount	Improved security bar, kensington Ic Auto source search, quick start, 8 c user logo, freeze, e-zoom, help, adv resistant design, PC and Mac comp 5°C to 35°C / 0 to 2,286 m (High alti 100 - 240 V AC ±10%, 50/60 Hz 228W (eco) 0.7W (eco) 3.1 kg 250 x 327 x 95 mm (excluding feet) 34 languages: English / French / Ge Hungarian / Czech / Romanian / Slovak / Chinese / traditional Chinese / Korea 3 m 1.8 m D-sub 15pin (Male / Male) 1.8 m USB-A to USB-B included included included included included included included ELPAP03 * ELPAP05 * ELPAP50 ELPAF22	olour modes, microphone input, moni anced test patterns, user button on re atible tude mode over 1,500 m) man / Italian / Spanish / Catalan / Po venian / Norvegian / Swedish / Finni Bulgarian / Malay / Wetnamese / Het	toring over network, SNMP, emote control, improved dust rtuguese / Dutch / Danish / Polish / sh / Russian / Ukrainian / Greek /			

\* Excludes EB-84H and EB-84L \*\* ISO 21118 based measurement

Chat: Fax:

0871 222 6702 (UK)\* 01 436 7742 (Republic of Ireland) enquiries@epson.co.uk etalk.epson-europe.com 0871 222 6740 Telephone: E-mail:

**3LCD** 

For more information please contact

\* Calls cost 10 pence per minute from a standard BT landline. Calls from other networks and mobiles may vary. Trademarks and registered trademarks are the property of Seiko Epson<sup>®</sup> Corporation or their respective owners. Product information is subject to change without prior notice.

Web:

**Better Products** 

for a Better Future

www.epson.co.uk www.epson.ie

EPSON WORLD LEADER IN PROJECTORS

No.1

### Epson EB-8H Series

#### Front view



#### Rear view



Screen size in inches	4:3 aspect ratio				
	Wide		Tele		
	cm	inch	cm	inch	
30	83	33	136	54	
40	111	44	182	72	
50	140	55	229	90	
60	169	66	275	108	
80	226	89	368	145	
100	283	111	460	181	
150	426	168	692	272	
200	568	224	923	363	
250	711	280	1155	455	
300	854	336	1386	546	

Screen size in inches	16:10 aspect ratio			
	Wide		Tele	
	cm	inch	cm	inch
30	85	33	140	55
40	118	47	193	76
50	149	58	243	95
60	179	70	292	115
80	239	94	390	153
100	300	118	488	192
150	451	178	733	289
200	603	237	979	385
250	754	297	1224	482
280	845	333	1371	540

